

CHEVRON™

**MEDIUM DUTY WRECKER
MODEL 1016**



STANDARD FEATURES

- Aluminum modular body sides with two tool compartments each side
- Aluminum 28 in. tunnel through box with tool compartment lights
- Tool compartment door closures on all doors
- 108, 120, 136 or 148 inch CA (must specify)
- 15,000 lb. Planetary winches
- 1/2 x 150 ft. cable
- Cable tensioners
- Hydraulic rear stabilizers
- 3 inch forks
- 4 inch forks
- Spring shackle adapters
- Low profile offset fork holders
- Underlift crossbar extensions
- Elevated fork holders
- Truck releasable L-arms
- Wheel straps and ratchets
- Tandem pump group
- Safety chain pockets
- Safety chains
- Slanted light pylon
- Electric wire remote control for underlift
- FMVSS 108 lighting
- Junction box with wire harness
- Pilot operated holding valves
- Lubrication fittings on all pivot points
- Dual rear controls
- Rear D-rings
- Tow light plug
- Backup alarm

OPTIONAL FEATURES

- J-hook chains
- PTO
- Trailer ball adapter
- Mudflaps
- Car releasable L-arms
- Radio Remote Control
- Glad Hand and seven pin connector
- Fifth wheel attachment
- Bar light
- Work lights
- Switch panel
- Magnetic tow lights
- Electric wire remote control for boom
- Pintle ball hitch adapter
- L.E.D. lights

CHASSIS RECOMMENDATIONS

| | 1016 |
|--|------------------------------|
| CA | 108, 120, 136 or 148 inch |
| Tire Size | 275/70R 22.5 |
| Minimum Frame Height | 36 inches |
| Maximum Frame Height | 40 inches |
| Minimum GVWR | 25,950 lbs. |
| Maximum GVWR | 33,000 lbs. |
| Minimum Frame RBM To 120" CA | 850,000 in • lbs each rail |
| Minimum Frame RBM Longer Than 120" CA | 1,200,000 in • lbs each rail |

NOTES:

Fuel tank position - back of fuel tank must be within 3 inches of back of cab. Preferred location for battery box is under the cab.

Tire size can be 295/75R 22.5 as long as the frame height does not exceed 40 inches.

Patents: Releasable L-Arm - #4,875,822

SPECIFICATIONS

| | |
|--|-----------------------------|
| Body width | 96 inches |
| Boom elevation | 40 degrees |
| Boom reach past tailboard | 93 inches |
| Underlift reach from tail board to center of fork | 87 inches |
| Negative tilt range | 10 degrees |
| Control valve | Sectional, 15 GPM, 2200 PSI |
| Oil reservoir | 20 gallons |
| Oil filters (2) | 12 GPM, 10 Microns |
| Tandem Pump | 15 GPM each port |

| | |
|---|---------|
| RATINGS* (lbs.) | 1016 |
| BOOM: | |
| • Retracted | 32,000 |
| • Extended | 12,000 |
| • Winch (1st layer) | 15,000 |
| - Wire Rope Working Limit, 1/2 in. diameter | 6,100 |
| - Standard Length | 150 ft. |
| UNDERLIFT: | |
| • Retracted | 12,000 |
| • Extended | 8,500 |
| • Tow Capacity (rolling) | 32,000 |
| • Car L-arms (paired) (optional) | 4,000 |
| • Truck L-arms (paired) | 6,000 |

* Load ratings are based on structural factors - not chassis capability or capacity.

Chevron reserves the right to improve or upgrade its products without obligation to modify previously manufactured units. This publication is printed in the U.S.A. and is the exclusive property of Chevron, Inc.



Distributed By:

Chevron, Inc.
7320 W. Market Street • U.S. Route 62 • Mercer, PA 16137
(724) 981-7500 • Toll Free (800) 886-6400 • FAX: (724) 981-4425
www.chevroninc.com