



# D.T.U.

## "Detachable Towing Unit"



The new Holmes D.T.U. (Detachable Towing Unit) offers proven design and technology from the oldest and most trusted name in the towing industry. The front legs allow the unit to be easily removed in a matter of minutes so your truck can be multi-functional for both towing or pulling trailers.

The D.T.U. is designed to secure to your truck using a front lock down bracket and your Fifth Wheel Plate. The power for the unit is provided by an optional wet line kit, with quick connect couplers, that is installed on your truck. Other popular options include a 20,000 lb. or 25,000 lb. planetary winch, tool boxes, and lanyard controls; all of which are available from your local Holmes distributor.



# DETACHABLE TOWING UNIT

## SPECIFICATIONS

Lift Capacity	
Retracted	.....35,000 lbs.
Extended	.....16,000 lbs.
Reach Past Tailboard	
Fully Extended	.....113 inches
Fully Retracted	.....51 inches
Power Tilt Arc	.....20°
Shipping Weight	
without winch	.....4,550 lbs.
with 20,000 Winch	.....5,000 lbs.

## STANDARD FEATURES & EQUIPMENT

- Power Elevation
- Power Extension
- Power Fold
- Power Tilt
- Front Stands
- Manual Controls
- 4 Sets of Frame Forks
- Fork Storage Holders
- Safety Chains
- Hook End Caps



## OPTIONAL EQUIPMENT

- 20,000 lb. Planetary Winch  
    150' x 9/16" IWRC Cable
- 25,000 lb. Planetary Winch  
    200' x 5/8" IWRC Cable  
(Winch Options Include: Air Tensioners, Air Free Spool, 360° Sheave Head, Air & Electrical Lines)
- Wet Line Kit  
    PTO with pressure relief valve, pump, 15 Gallon Hydraulic Tank, Return Filter, Quick Disconnect, Fittings & Hoses
- Hand Held Remote Control  
    6 Function Controller with 25' Cord
- Emergency Lighting
- Work Area Lighting
- Remote Tailboard Control
- Switch Panel
- Tow Lights & Cord
- Tool Compartment
- Additional Lift Forks & Towing Attachments



Note: Some optional equipment may be shown. Other Holmes Towing & Recovery Equipment is Available from your local Holmes Distributor.

## CHASSIS RECOMMENDATIONS

Minimum Wheelbase ..... 250"

Min. Clearance from front of D.T.U. to Center of Trunnion 84"

Note: Ratings are based on structural factors only - not chassis capacity. All chassis specifications are minimums, heavier specifications may be required depending on chassis and equipment weights. Holmes reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability.



## Proven Design & Technology



8503 Hilltop Dr. • Ooltewah, TN 37363  
Phone: (800) 489-2401 • (423) 238-4171  
Fax: (800) 960-6667  
www.millerind.com

DISTRIBUTED BY: