



V-30



Optional Equipment May Be Shown.

Power, Performance, and Value

Vulcan pioneered integrated towing and recovery equipment in North America over a decade ago with the introduction of the Vulcan 940. That spirit of innovation is still found today in the Vulcan V-30. This versatile medium duty model is ideally suited to handle a wide range of vehicles from passenger cars, medium duty trucks, city tractors, and motor homes in both towing and recovery applications. Contact your local Vulcan Distributor to find out how the Vulcan V-30 can help increase your profits by handling your tough business demands.

***Innovative. Durable.
Brutally Tough.***

Innovative. Durable. Brutally Tough.

STANDARD FEATURES

- 120" Aluminum Modular Body
- Three Compartments Per Side
- Pass Thru Tunnel Box with 48" Suicide Doors
- Lift Fork Storage, Driver & Passenger Side
- Adjustable Shelves
- Manual Driver's Side Controls
- Passenger Side Lanyard Control for Underlift
- Hydraulic Rear Jacks with Flipper Feet
- Tailboard D-Rings
- Safety Chains in the Tailboard
- Planetary Winches
- Winch Air Free Spool
- Spring Cable Tensioners
- Dual Hydraulic Pump
- Three Sets of Lift Forks
- 4,000 lb. Strapless Wheel Retainers (Opt. with VX2 body)
- 6,500 lb. Strapless Wheel Retainers
- LED Body Lighting
- Tool Compartment Lighting
- Gas Door Shocks
- Mud Flaps



Standard 120" CA Aluminum Body shown with Optional-Equipment.

BOOM SPECIFICATIONS

Retracted at 30°	32,000 lbs.
Extended at 30°	12,000 lbs.
Maximum Lift Angle	36°
Maximum Hook Height	160"
Reach Past Tailboard at 30°	54"

WINCH RATING & CABLE

Rating (first layer of drum) each Winch	15,000 lbs.
Diameter and Length (each winch)	1/2" x 150'
Cable Type6 x 37 IWRC

OPTIONAL EQUIPMENT

- VX2 Low Profile Body
- Steel Light Pylon
- Emergency Lighting
- Manual Controls - Passenger Side
- Air & Electrical Hookups
- Additional Lifting Attachments
- Many Other Popular Vulcan Options
- Air Shift PTO
- Work Lights
- In Cab Controls
- Wide Load Light Bar
- Hand Rails
- Installation



UNDERLIFT SPECIFICATIONS

Retracted with Forks	12,000 lbs.
Extended with Forks	8,500 lbs.
Extended with Wheel Retainers	4,000 lbs. / 6,500 lbs.
Maximum Reach to Center of Forks	
At the Normal Tow Height	84"
Positive Tilt	20°
Negative Tilt	10°
Tow Rating	32,000 lbs.

CHASSIS RECOMMENDATION

GVWR	26,500 - 30,000 lbs.
Maximum Frame Height	38"
Maximum Tire Size	255/70 R 22.5
Clear C.A.	120"

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.



The Vulcan V-30-VX2 body option provides a low profile 120" CA aluminum modular body with external mounted drivers side controls. Three compartments per side along with a 24" pass through tunnel box and drivers side fork storage provide ample space for your equipment storage.

DISTRIBUTED BY:



©2008 Miller Industries Towing Equipment Inc. All Rights Reserved.



8503 Hilltop Drive • Ooltewah, TN 37363
 800-489-2401 • 423-238-7227
 FAX 800-960-6667 • www.MILLERIND.com