

CHEVRON™

**LIGHT DUTY WRECKER
MODEL 408/410/412**





Chevron's optional pivoting L-arm system lets you hook up fast and damage free. Light weight L-arms with horizontal pivoting receivers allow for a quick, efficient hookup even if the wheels are turned.

STANDARD EQUIPMENT

- Two side entry tool boxes
- FMVSS 108 lighting
- Junction box and wire harness
- Safety chain pockets
- Dual rear controls
- Rear chain anchors
- Tow light plug
- Wheel straps
- 8 inch sills
- Cable tensioner (with winch)
- Releasable L-arms
- Rear enclosed wheel wells
- Pilot operated holding valves
- Lubrication fittings on all pivot points
- Safety chains
- Backup alarm
- In prime
- Mudflaps
- Direct mount pump
- L.E.D. lights

MODEL	408	410	412
Boom	8 Ton Low Profile	10 Ton Low Profile	12 Ton High Profile
Winch Capacity	9,000 lb. Planetary	12,000 lb. Planetary	12,000 lb. Planetary
Cable	3/8 x 100	7/16 x 150	7/16 x 150

OPTIONAL EQUIPMENT

- Pivoting L-arm
- AutoGrip™ II Wheel Lift
- Light pylon
- Slanted light pylon
- Jumbo lighted tunnel tool box
- Stainless steel body side panels
- In cab electric remote controls
- Rear wheel fender flares
- PTO
- Clutch pump
- Radio remote control

ACCESSORIES

- Bar light
- Work lights
- Switch panel
- Magnetic tow lights
- Tow sling
- J-hook chains
- Frame fork holders
- 3 inch frame forks
- Pintle hook attachment
- Trailer hitch adaptor
- Push bumper



Chevron's optional AutoGrip™ II wheel lift allows the wheel retainer arms to hydraulically rotate from a fully closed storage position to a fully open approach position.

CHASSIS RECOMMENDATIONS

	408/410/412
CA	60, 84
Minimum GVWR	11,000 lb.
Maximum GVWR	22,000 lb.
Maximum Frame Height	35 inches
Minimum Frame RBM	280,000 in • lbs

SPECIFICATIONS

Body width	86 inches
Boom elevation	45 degrees
Boom reach	63 inches
Underlift reach	67 inches
Power tilt range	+8 degrees and -7 degrees
Control valve-boom	Sectional, 20 GPM, 1700 PSI
Control valve-underlift	Sectional, 12 GPM, 1700 PSI
Oil reservoir	12 gallons
Oil filter	250 PSI, 15 GPM, 10 Microns
Direct mount pump	18 GPM @ 1200 RPM
Clutch pump	9 GPM @ 1250 RPM

RATINGS* (lbs.)	408	410	412
BOOM:			
• Retracted	16,000	20,000	24,000
• Extended	6,000	8,000	10,000
UNDERLIFT			
• Retracted (Forks)	6,000	6,000	6,000
• Extended	4,000	4,000	4,000
• L-arms (Paired)	4,000	4,000	4,000
• Tow	10,000	10,000	10,000

* Load ratings are based on structural factors - not chassis capability or capacity.

Chevron reserves the right to improve or upgrade its products without obligation to modify previously manufactured units. This publication is printed in the U.S.A. and is the exclusive property of Chevron, Inc.

Chevron, Inc.

7320 W. Market Street • U.S. Route 62 • Mercer, PA 16137
(724) 981-7500 • Toll Free (800) 886-6400 • FAX: (724) 981-4425
www.chevroninc.com