

FRF *FOLDING RAMP FLATBED*



millerind.com

Miller
INDUSTRIES

STANDARD EQUIPMENT

- 28' - 102" Wide , 30,000 lb. Deck
- Deck Height above Chassis Frame - 5.5"
- Steel & Apitong Wood Flooring
- Fully Fabricated Heavy-Duty Steel Subframe
- Hydraulic Tail & Ramp Lock
- 24 Chain Locks & 2 D-Rings (Mounted at Winch)
- Floor Level Sides
- Drivers Side Controls
- Wireless Controller
- 20,000 lb. Planetary Winch
- Winch Air Free Spool
- Bed Mounted Ladder
- Painted in Black Acrylic Enamel
- Reese Style Receiver & 7-Way Trailer Plug
- Body Wiring Harness & Junction Box
- Federal #108 Lighting

DECK SPECIFICATIONS

- Main - 226" (To Center of Pivot Pin)
- Middle Section - 114 3/4" (To Center of Pivot Pin)
16,000 lb. Lift Capacity (Based on an Equally Distributed Load)
- Tail - 60"



OPTIONAL EQUIPMENT

- Bed Mounted Cab Protector
- Additional Chain Locks
- Additional D-Rings
- Optional Body Color (Top & Sides)
- Anti-Skid Paint - Top & Sides
- Front Mud Flaps & Brackets
- 62" 10 Head LED Lightbar
- 48" Toolbox with Stainless Steel Door
- Winch Guard
- Locking Chain Racks (Cab Protector Mounted)
- Chain Binder Storage (Cab Protector Mounted)
- Safety Cones & Storage Brackets
- Dual Reverse Camera
- Rightway Scale System
- Installation



CHASSIS RECOMMENDATIONS

Minimum GVW	*56,500 lbs.
Minimum Frame RBM (each Rail)	3.0 Million Inch-Pounds
Suggested Tire Size	
Front	315/80R22.5
Rear	295/75R22.5
Minimum Frame Section Height	11.5"
Minimum Cab to Bogie (clear)	**190"
Minimum After Frame (rear axle)	65"

*Consult the Factory for other GVW

**Use back of vertical exhaust for the usable CB and effective back of cab.

All ratings are based on structural factors only, not vehicle(chassis) capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.

